

AD-A121 167


ENGINEER MODELING STUDY VOLUME II USERS MANUAL(U)  
CONSTRUCTION ENGINEERING RESEARCH LAB (ARMY) CHAMPAIGN  
IL G BROWN ET AL. SEP 82 CERL-TR-P-131-VOL-2


1/1

UNCLASSIFIED

F/G 15/7

NL





MICROCOPY RESOLUTION TEST CHART

40x

construction  
engineering  
research  
laboratory



United States Army  
Corps of Engineers  
...Serving the Army  
...Serving the Nation

12  
TECHNICAL REPORT P-131  
September 1982  
Engineer Modeling Study

ENGINEER MODELING STUDY VOLUME II:  
USERS MANUAL

ADA 121167

by  
Gerald Brown  
Hugh Henry



Approved for public release; distribution unlimited.

The contents of this report are not to be used for advertising, publication, or promotional purposes. Citation of trade names does not constitute an official indorsement or approval of the use of such commercial products. The findings of this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

*DESTROY THIS REPORT WHEN IT IS NO LONGER NEEDED  
DO NOT RETURN IT TO THE ORIGINATOR*

**SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)**

DD FORM 1 JAN 73 1473 EDITION OF 1 NOV 68 IS OBSOLETE

**SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)**

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

BLOCK 20. (CONTINUED)

This volume lists the program input requirements for the Engineer Module and describes how to interpret program results. Error messages and a bibliography are included.

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE(When Data Entered)

## FOREWORD

This study was performed for the Directorate for Combat Developments (DCD), U.S. Army Engineer School (USAES), under Project 4A762731AT41, "Military Facilities Engineering Technology"; Task D, "Combat Engineering Strategy"; Work Unit 048, "Engineering Modeling Study." The USAES/DCD Technical Monitor was CPT Clifford Clausen.

The study was conducted by the Facility Systems (FS) Division of the U.S. Army Construction Engineering Research Laboratory (CERL). CERL personnel directly involved in the study were Dr. Gordon Bagby, Mr. Gerald Brown, Mr. Carlton Mills, Mr. Theodore Tourlentes, and 1LT Hugh Henry. Appreciation also is expressed to Professor John Boyd of Knox College, Galesburg, IL, for his help with this work. Mr. Edward Lotz is Chief of CERL-FS.

COL Louis J. Circeo is Commander and Director of CERL, and Dr. L. R. Shaffer is Technical Director.



## CONTENTS

	Page
DD FORM 1473	1
FOREWORD	3
1 INTRODUCTION .....	5
Background	
Objective	
2 DATABASE—AN OVERVIEW .....	6
Engineer Systems	
Techniques	
Tasks	
Single Job Orders	
Multiple Job Orders	
Standard Requirements Code	
Engineer Units	
Tactical Units	
Order Stream	
PROCFIL/PSEUPROC.OLD	
Assignment File (DEC VAX 11/780 Only)	
Operating Procedures (Boeing Cyber Computer Only)	
Operating Procedures (DEC VAX 11/780 Only)	
3 OUTPUT .....	23
APPENDIX A: Bibliography	28
APPENDIX B: Simulation Control Errors	29
DISTRIBUTION	



## ENGINEER MODELING STUDY VOLUME II: USERS MANUAL

# 1 INTRODUCTION

### Background

Existing Army war games are good at representing unit offensive and defensive movements, but weak in measuring the contribution of combat engineer activities to the combined arms team. The value and effectiveness of engineer fortifications and barriers are well known, but current models ignore the combat engineers completely, confining engineer representation to obstacle effects, or estimating their efforts by extrapolation using a post-processor.<sup>1</sup>

In 1979, the U.S. Army Engineer School (USAES), representing the Training and Doctrine Command (TRADOC), asked the U.S. Army Construction Engineering Research Laboratory (CERL) to correct this deficiency. The Engineer Module, developed under CERL's Engineer Modeling Study (EMS), was the result. This volume is the second in a three-volume report which documents the capabilities and use of CERL's Engineer Module. The other volumes are:

Volume I: Executive Summary

Volume III: CORDIVEM/Engineer Module Interface Manual

This volume provides the information necessary to prepare data for input to the Engineer Module, run the module in the stand-alone mode (without CORDIVEM interface), and understand the module's output.

The Engineer Module is data-driven. This allows the user to make different computer runs by changing the data base, rather than by changing the program code. This makes it easy for the user to simulate new engineer systems, new engineer tactics, and different command and control relationships. Since there will always be more requests for engineer resources than there are engineer resources available, the user must input automatic prioritization data to allocate resources among competing requests. The allocation of resources then will vary, depending on the user's situation and the prioritization data.

Because the Engineer Module is data-driven, the user must input a considerable amount of data before the model will run. Once the data are loaded into computer files, a text editor is used to modify the data base for subsequent runs.

### Objective

The overall objectives of this study were:

1. To model the contribution of friendly and enemy engineers to the effectiveness of the combined arms team.
2. To represent, with accuracy and consistency, the effectiveness of the combat engineer effort throughout the Army Model Improvement Program (AMIP) model hierarchy.

<sup>1</sup> *Engineer Family of Systems Study (E-FOSS)* (U.S. Army Engineer School, 1979); *The Value of Field Fortification in Modern Warfare* (Historical Evaluation and Research Organization, 1979); and *Historical Evaluation of Barrier Effectiveness* (Historical Evaluation and Research Organization, 1974).

3. To develop a system that the USAES and other agencies can use to (a) review modeling data so new equipment or doctrine can be incorporated easily, and (b) support the evaluation of hypothetical equipment or doctrine.

The objective of this volume is to (1) explain how to use CERL's Engineer Module, (2) help the user prepare program input, and (3) help the user interpret program results.

## 2 DATABASE—AN OVERVIEW

Eight major sections comprise the Engineer Module input:

1. Engineer Systems (ESY)
2. Techniques (TEC)
3. Tasks (TSK)
4. Single Job Orders (SJO)
5. Multiple Job Orders (MJO)
6. Standard Requirements Code (SRC)
7. Engineer Units (EUT)
8. Tactical Units (TUT).

Each of these sections is a separate computer file. Each file is identified by an input section acronym and up to a three-character prefix, e.g., (xxx) SJO. Throughout this volume, the symbols "<" and ">" will bracket names for user-defined input. That is, (xxx) SJO is a notation for a six-character file name. The first three characters are defined by the user, but the system requires that the last three characters be SJO. For instance, if the user wants two test files, the files may be named T01SJO and T02SJO. User names like TEST1 and TEST2 violate the (xxx) SJO convention, and any attempts to use them will cause problems. (When using the VAX 11/780, file names should be followed by a period and the letters DAT. For example, the tasks file could be named D86TSK.DAT.) The Engineer Module's data structure is shown in Figure 1.

An interactive editor or a punch card system may be used to create these files. If the user is unfamiliar with such systems, one of the following manuals may be consulted.

For Boeing Cyber users:

*MAINSTREAM-EKS Interactive Timesharing (KIT) Users Manual* (Boeing Computer Services Inc., 1977)

For DEC/VAX 11/780 users:

*VAX/VMS Users Manual, Volume 3A* (Software Distribution Center, Digital Equipment Corporation, 1980).

The following paragraphs briefly describe each of the major input sections.




Figure 1. Engineer Module data structure hierarchy.

#### Engineer Systems

An engineer system is the basic element modeled by the Engineer Module, i.e., a CEV, D-7, or SQUAD. At present, the only attribute of an engineer system is velocity, since it must travel from its unit to the work site. Data on engineer systems and their velocity may be obtained from the Engineer Family of Systems Study (E-FOSS) report or threat data (see Appendix A).

### *Engineer Systems: Input Instructions*

1. Engineer System Name (10-character maximum)
2. Engineer System Move Rate (km/hr)

NOTE: REPEAT 1 AND 2 FOR EACH SYSTEM.

### *Engineer Systems: Sample Data*

SQUAD	(engineer system name)
50	(velocity in km/hr)
D-7	(engineer system name)
35	(velocity in km/hr)
ACE	(engineer system name)
45	(velocity in km/hr)
CEV	(engineer system name)
45	(velocity in km/hr)
2.5LOADER	(engineer system name)
35	(velocity in km/hr)
AVLB	(engineer system name)
45	(velocity in km/hr)
50M.BRIDGE	(engineer system name)
50	(velocity in km/hr)
SLUFAE	(engineer system name)
45	(velocity in km/hr)
GEMSS	(engineer system name)
45	(velocity in km/hr)

### **Techniques**

A graph or network of activities is used to represent engineer techniques such as CONSTRUCT 5 DEFILADES -- CEV. The input consists of a description of the graph (node number, successor and predecessor nodes) and the resources required. An example of an engineer network which might be modeled is shown in Figure 2. Data on combat engineer techniques, resources, and time estimates may be obtained from appropriate Army Training and Evaluation Program (ARTEP) publications and Army Field Manuals (see Appendix A).

### *Technique: Input Instructions*

1. Technique Name (50-character maximum)
2. Number of Resources

## **BLOW AN AUTOBAHN BRIDGE**



Figure 2. Example engineer network.

3. Resource Identification Number and Minimum Time to Completion (minutes)

4. Resource Name (must be an engineering system)

NOTE: REPEAT 3 AND 4 FOR EACH RESOURCE.

5. Number of nodes

6. A. Node Type - M.WS/M.ASP/L/W - Move to Work Site, Move to Ammunition Supply Point (ASP), Load, Work

B. Node Number

C. Time (minutes) or Move Rate (km/hr)

D. Number of Predecessors

7. Number of Active Resources (list of resource identification numbers)

8. Number of Released Resources (list of resource identification numbers)

9. Number of Successor Nodes (list of successor nodes)

NOTE: REPEAT 6 THROUGH 9 FOR EACH NODE.

WHEN NODE TYPE (ITEM 6A) IS M.WS OR M.ASP, ITEM 6C DESCRIBES MOVE RATE.

WHEN NODE TYPE IS L OR W, ITEM 6C DESCRIBES MINUTES TO NODE COMPLETION.

*Technique: Sample Input Data*

BLOW AN AUTOBAHN BRIDGE (technique name)

1	(number of resources)
1 210	(resource identification number, number of minutes to technique completion)
SQUAD	(resource name)
4	(number of nodes)
M.ASP 1 50 0	(node type, node number, move rate in km/hr, number of predecessor nodes)
1 1	(number of active resources, resource identification number[s])
0	(number of released resources)
1 2	(number of successor nodes, successor node number[s])
L 2 30 1	(node type, node number, number of minutes to node completion, number of predecessors)
1 1	(number of active resources, resource identification number[s])
0	(number of released resources)
1 3	(number of successor nodes, successor node number[s])
M. WS 3 50 1	(node type, node number, move rate in km/hr, number of predecessors)
1 1	(number of active resources, resource identification number[s])
0	(number of released resources)
1 4	(number of successor nodes, successor node number[s])
W 4 180 1	(node type, node number, minutes to node completion, number of predecessors)
1 1	(number of active resources, resource identification number[s])
1 1	(number of released resources, resource identification number[s])
0	(number of successor nodes)

# CONSTRUCT 5 DEFILADES - TANK OR APC - ACE (technique name)

1 (number of resources)  
 1 135 (resource identification number, number of minutes to technique)  
 ACE (resource name)  
 2 (number of nodes)  
 M.WS 1 50 0 (node type, node number, move rate in km/hr, number of predecessors)  
 1 1 (number of active resources, resource identification number[s])  
 0 (number of released resources)  
 1 2 (number of successor nodes, successor node identification number[s])  
 W 2 135 1 (node type, node number, number of minutes to node completion or number of predecessors)  
 1 1 (number of active resources, resource identification number[s])  
 1 1 (number of released resources, resource identification number[s])  
 0 (number of successor nodes)

## Tasks

Techniques which have similar results are grouped into tasks. For example, the task CRATER ROAD might use the techniques M180 or SHAPED/CRATER CHARGE. The user must define the default technique selection and battlefield importance rating of single task orders. For each single task order, the user selects a list of techniques that could fulfill the single task order, grades each technique according to how appropriate or desirable it is (Table 1), and rates the order's battlefield importance for different situations (Table 2).

The user can vary the grading and rating of techniques for a task depending on the situation. For example, when there is no enemy threat, the user may wish to use D-7s to dig defilades. When there is an enemy threat, he may choose the ACE since it provides armor protection for the operator. Depending on the data available and other constraints, the situation could be defined by one of the two methods shown in Figure 3. Other

Table 1  
The Task/Technique Grading Scale

GRADE	MEANING
A	Preferred technique and preferred use of resources
B	Same as A, but somewhat less effective or preferable
C	Effective/nonstandard choices, but not the optimum
D	Ineffective technique or dangerous given the situation/location
E	Same as D, but less desirable

Each engineering task and technique must be graded on its effectiveness. The model will always attempt to select the highest graded technique consistent with what resources are available and when the job must be completed.

The grade impacts the scheduling algorithm and the generation of unit movement orders. Current plans are to continue searching up the chain of command until resources for a Grade A or B technique are found. Otherwise, a Grade C, D, or E technique will be selected. Grade D or E tasks/techniques must always use the company's internal resources. Thus, no unit move orders will be issued from battalion to the company to perform such low-grade task/techniques; these jobs will be queued until resources become available.

It will not always be necessary to provide an entry for each grade: some jobs may have only A or B alternatives.

**Table 2**  
**Estimated Consequence to Mission Success**  
**of Not Receiving Engineer Support (Priority)**

Priority Rating Scale	Severity Description	How Commanders Will Perceive the Consequences of Not Receiving Engineer Support
1	None (lowest priority)	Unit ability to accomplish the mission is not degraded. An alternate "non-engineer" technique of equal effectiveness can be employed. For example, the commander perceives unit tanks can be concealed in local terrain. Lack of engineer support to dig tanks in should not prevent unit from defending the area.
2		
3		
4	Moderate	Unit ability to accomplish the mission is moderately degraded. Commander diverts unit assets from their primary mission to accomplish engineer tasks for which they are not trained or equipped. For example, lack of engineer support requires infantry soldiers to cut trees at a roadblock instead of improving TOW positions servicing the obstacle. As a result, the TOWs may service fewer targets before being discovered and suppressed.
5		
6		
7	Significant	Unit ability to accomplish the mission is significantly degraded. Commander is forced to deploy a material system in a dangerous or ineffective manner. For example, lack of engineer support at a forward arming and refueling point reduces the servicing capacity of the point and decreases its survivability.
8		
9	Serious (highest priority)	Unit ability to accomplish mission is affected to the extent the mission may be aborted. For example, without engineer support the commander determines time is not adequate to develop a strongpoint defense which was determined the only defense tactic possible against threat forces in that area.

factors that could help define situations are offensive or defensive operations, dirty-battlefield conditions, day or night, etc. The inclusion of many factors to define the situation will expand data input requirements, the size of the data base, and the simulation run time.

This is a default mechanism only. Orders can be given with explicit priority. However, a default mechanism is needed to reduce the workload on the engineer gamer.

The user must resolve four separate issues:

1. Define *situations*.
2. Rank alternative *techniques* for each situation.
3. Identify *task groupings* and assign them priorities for each situation.
4. Identify (on an exception basis) how threat engineer tactics differ from those used by U.S. engineer units.

The rankings so obtained will be used by the Engineer Module to allocate engineer resources when more than one task has been assigned to a particular unit.

**Task: Input Instructions**

1. Task Name (30-character maximum)

**EXAMPLE A****DISTANCE FROM SUPPORTED MANEUVER UNIT TO WORKSITE**

	$\leq 7 \text{ Km}$	$> 7 \text{ Km}$
CONTACT WITH ENEMY	1	2
NO CONTACT WITH ENEMY	3	4

**EXAMPLE B**

TERRAIN TYPE	SITUATION
URBANIZED	1
FORESTED	2
MOUNTAINOUS	3
OPEN	4

**Figure 3.** Example situation definition.

2. Number of Situation Ranges
3. First Situation Last Situation (range for techniques)
4. Number of Techniques for Range

5. Technique Name

6. Grade (Valid A, B, C, D, or E; see Table 1)

NOTE: REPEAT 5 AND 6 FOR EACH TECHNIQUE. REPEAT 3, 4, 5, AND 6 FOR EACH RANGE.

7. Two-Character Code for Task

8. Number of Situation Ranges (for priority class assignment)

9. First Situation Last Situation Priority (See Table 2 for priority codes)

NOTE: REPEAT 9 FOR EACH SITUATION RANGE.



*Task: Sample Input Data*

CONSTRUCT 5 HULL DEFILADES (task name)  
1 (number of situation ranges)  
1 1 (first situation, last situation)  
3 (number of techniques for range)  
CONSTRUCT 5 DEFILADES TANK OR APC ACE (technique name)  
A (grade)  
CONSTRUCT 5 DEFILADES TANK OR APC CEV (technique name)  
A (grade)  
CONSTRUCT 5 DEFILADES TANK OR APC D-7 (technique name)  
A (grade)  
SA (two-character code for task)  
1 (number of situation ranges)  
1 1 5 (first situation, last situation, priority)

**Single Job Orders**

Tasks which have similar results are grouped to form single job orders. For example, the order BLOCK ROAD might use the tasks CRATER ROAD or CONSTRUCT ABATIS. The data input structure for single job orders is the same as it is for tasks. The user must grade and assign a priority to each task.

*Single Job Order: Input Instructions*

1. Single Job Order Name (30-character maximum)
2. Number of Situation Ranges
3. First Situation Last Situation (range for tasks)
4. Number of Tasks for Range
5. Task Name
6. Grade (Valid A, B, C, D, or E; see Table 1)

NOTE: REPEAT 5 AND 6 FOR EACH TASK. REPEAT 3, 4, 5, AND 6 FOR EACH RANGE.

7. Two-Character Code for Single Job Order (optional)
8. Number of Situation Ranges (for priority class assignment)
9. First Situation Last Situation Priority (see Table 2 for priority codes)

NOTE: REPEAT 9 FOR EACH SITUATION RANGE.

*Single Job Order: Sample Input Data*

In this sample, input data for four situations were defined as shown in Example B, Figure 3.

BLOCK ROAD (single job order name)  
3 (number of situation ranges)  
1 1 (first situation, last situation)

2       *(number of tasks for range)*  
 RUBBLE STREET   *(task name)*  
 A       *(grade)*  
 CRATER ROAD     *(task name)*  
 A       *(grade)*  
 2 3     *(first situation, last situation)*  
 3       *(number of tasks for range)*  
 CONSTRUCT ABATIS *(task name)*  
 B       *(grade)*  
 CRATER ROAD     *(task name)*  
 A       *(grade)*  
 BUILD LOG CRIB   *(task name)*  
 B       *(grade)*  
 4 4     *(first situation, last situation)*  
 2       *(number of tasks for range)*  
 POINT MINEFIELD *(task name)*  
 A       *(grade)*  
 CRATER ROAD     *(task name)*  
 A       *(grade)*  
 CB       *(two-character code)*  
 2       *(number of situation ranges for priority class assignment)*  
 1 3 9   *(first situation, last situation, priority)*  
 4 4 6   *(first situation, last situation, priority)*

#### **Multiple Job Orders**

The user may wish to group single job orders by situation to produce a desired result. For example, the order CONSTRUCT STRONGPOINT might consist of the single job orders CRATER ROAD, DIG DEFILADES, CONSTRUCT MINEFIELDS, and CONSTRUCT ANTI-TANK DITCHES. The order, quantity, and priority of the single job orders may vary depending on the situation, and must be specified by the user.

#### *Multiple Job Order: Input Instructions*

1. Multiple Job Order Name (30-character maximum)
2. Number of Situation Ranges
3. First Situation   Last Situation (range for single job orders)
4. Number of Single Job Orders for Range
5. Single Job Order Name
6. Priority (see Table 2 for priority codes)

NOTE: REPEAT 5 AND 6 FOR EACH SINGLE JOB ORDER. REPEAT 3, 4, 5, AND 6 FOR EACH RANGE.

#### *Multiple Data Job Order: Sample Data*

BATTLE POSITION TYPE 1       *(multiple job order name)*  
 1       *(number of situation ranges)*  
 1 1     *(first situation, last situation)*  
 3       *(number of single job orders for range)*

CONSTRUCT 5 HULL DEFILADES (single job order name)  
 5 (priority)  
 CONSTRUCT 5 HULL DEFILADES (single job order name)  
 5 (priority)  
 CONSTRUCT 500 M. ANTITANK DITCH (single job order name)  
 5 (priority)

#### Standard Requirements Code

The standard requirements code is similar to the Tables of Organization and Equipment (TOE) in that the type and quantity of basic engineer systems are input for each type of engineer unit. The user must specify standard requirements codes for both friendly and enemy forces.

#### Standard Requirements Code: Input Instructions

1. Standard Requirements Code Name (30-character maximum)
2. Color (Blue or Red)
3. Number of Systems
4. Engineer System Name
5. Quantity

NOTE: REPEAT 4 AND 5 FOR EACH SYSTEM IN THE STANDARD REQUIREMENTS CODE.

#### Standard Requirements Code: Sample Input Data

ENG.PLT.DIV	(standard requirements code name)
BLUE	(color)
3	(number of systems)
SQUAD	(system name)
3	(quantity)
SQUAD	(system name)
3	(quantity)
CEV	(system name)
1	(quantity)
ACE	(system name)
2	(quantity)
ENG.CO.POOL	(standard requirements code name)
BLUE	(color)
4	(number of systems)
2.5.LOADER	(system name)
1	(quantity)
GEMSS	(system name)
1	(quantity)
AVLB	(system name)
6	(quantity)
SLUFAE	(system name)
2	(quantity)
NONE	(standard requirements code name)
BLUE	(color)
0	(number of systems)

NOTE: THE USER MUST INCLUDE A STANDARD REQUIREMENTS CODE NAMED NONE WHICH HAS 0 SYSTEMS. THIS IS THE STANDARD REQUIREMENTS CODE OF THE HIGHEST LEVEL HEADQUARTERS UNIT.

#### Engineer Units

An engineer unit's assets are defined by its standard requirements code. Several engineer units may have the same code. The engineer unit input requires the user to establish command and control relationships (pointers to the parent engineer unit and the supported tactical unit) as well as X and Y coordinates on the battlefield for both U.S. and threat forces. These coordinates express distance in kilometers from a user-defined point. Although many different standard requirements codes may be used in a simulation run, Red and Blue engineer forces are each limited to two levels of command and control. For example, the user may define engineer platoon/engineer company or engineer battalion/engineer brigade relationships, but not an engineer platoon/engineer company/engineer battalion relationship.

#### Engineer: Unit Input Instructions

1. Engineer Unit Name (20-character maximum)
2. Standard Requirements Code Name
3. Color (Blue or Red)
4. Parent Engineer Unit Pointer
5. Supported Tactical Unit Pointer
6. X-Location Y-Location (kilometers)

NOTE: REPEAT 1 THROUGH 6 FOR EACH ENGINEER UNIT.

#### Engineer Unit: Sample Input Data

1ST.PLT.A.CO	(engineer unit name)
ENG.PLT.DIV	(standard requirements code name)
BLUE	(color)
5 1	(parent unit, supported tactical unit)
32.003 33.637	(X coordinate, Y coordinate)
2ND.PLT.A.CO	(engineer unit name)
ENG.PLT.DIV	(standard requirements code name)
BLUE	(color)
5 2	(parent unit, supported tactical unit)
29.541 31.050	(X coordinate, Y coordinate)
3RD.PLT.A.CO	(engineer unit name)
ENG.PLT.DIV	(standard requirements code name)
BLUE	(color)
5 3	(parent unit, supported tactical unit)
30.551 27.624	(X coordinate, Y coordinate)
A.CO.POOL	(engineer unit name)
ENG.CO.DIV.(+).POOL	(standard requirements code name)
BLUE	(color)
5 0	(parent unit, supported tactical unit)
26.069 31.888	(X coordinate, Y coordinate)

A.CO.HQ	(engineer unit name)
NONE	(standard requirements code name)
BLUE	(color)
0 0	(parent unit, supported tactical unit)
26.069 31.888	(X coordinate, Y coordinate)

#### **Tactical Units**

The user must enter the name of the tactical unit and parent and supporting engineer unit pointers to establish a command and control relationship for allocating engineer resources. The data field should contain inputs for both friendly and enemy forces.

#### *Tactical Unit: Input Instructions*

1. Tactical Unit Name (20-character maximum)
2. Color (Blue or Red)
3. Parent Tactical Unit Pointer
4. Supporting Engineer Unit Pointer

NOTE: REPEAT 1 THROUGH 4 FOR EACH TACTICAL UNIT.

#### *Tactical Unit: Sample Input Data*

5TH.BN.1ST.BDE	(tactical unit name)
BLUE	(color)
4 1	(parent unit, supporting engineer unit)
6TH.BN.1ST.BDE	(tactical unit name)
BLUE	(color)
4 2	(parent unit, supporting engineer unit)
7TH.BN.1ST.BDE	(tactical unit name)
BLUE	(color)
4 3	(parent unit, supporting engineer unit)
1ST.BDE	(tactical unit name)
BLUE	(color)
0 4	(parent unit, supporting engineer unit)

#### **Order Stream**

After all eight major data sections have been defined and entered into corresponding data files, the user must create a job file, (xxx) JOBS, to exercise the Engineer Module. Each record in the file will be an individual job, with a name, start and finish time, X and Y location, and a requestor and situation code.

#### *Order Stream: Input Instructions*

1. External Event (RCRD on Cyber, RECEIVE.ORDER on VAX)
2. Start Time (day hour minute)
3. Order Name (single job order or multiple job order)
4. Five-Character Order Abbreviation

5. X Location Y Location
6. Late Finish/Deadline Time (day hour minute)
7. Requestor (tactical unit pointer)
8. Situation
9. Optional override of default priority (see Table 2 for priority codes)
10. \*

NOTE: REPEAT 1 THROUGH 10 FOR EACH ORDER.

*Order Stream: Sample Input Data*

External Event	(RCRD on Cyber, RECEIVE.ORDER on VAX)
0 0 0	(start time day, hour, minute)
CRATER ROAD	(order name)
CRTRD	(order abbreviation)
132 136.8	(X location, Y location)
1 0 0	(late finish time day, hour, minute)
1	(requestor)
1	(situation)
*	

External Event	(RCRD on Cyber, RECEIVE.ORDER on VAX)
0 0 0	(start time day, hour minute)
CRATER ROAD	(order name)
CRTRD	(order abbreviation)
133.8 106.2	(X location, Y location)
1 0 0	(late finish time day, hour, minute)
1	(requestor)
1	(situation)
*	

**PROCFIL/PSEUPROC.OLD**

After the eight data and order files are created, the user must make system assignments that relate these files to predesignated file numbers in the operating procedure file. The operating procedure file is named PROCFIL when using the Boeing Cyber computer and PSEUPROC.OLD when using the VAX 11/780. Some additional data also must be input in order to initialize data arrays.

The number of situations and ammunition supply points may vary, and must be input by the user. Since the user has created the eight data files, the program must be initialized with the number of systems, techniques, tasks, single job orders, multiple job orders, standard requirements codes, engineer units, and tactical units created. The user then must assign these files the numbers 9, 11, 13, 15, 17, 19, 21, and 23. These numbers correspond to internal program file numbers (see Volume III). Thus, the (xxx) ESY file becomes the internal program file SIMU09, the file (xxx) TEC becomes the internal file SIMU11, etc. The file SIMU25 is reserved for interface data required between the Engineer Module and CORDIVEM (see Volume III).

Report flags (0 or 1) are used to echo input as output, if so desired. A 0 means suppress output and a 1 means print input as output for each data file used. Since some of

the data files may be quite large, the user may wish to condense output by using the report flags to suppress the printout of files which were not changed between program runs.

The output level (10, 20, 30, 40 or 50) corresponds to the detailed level of information which the user wishes to see as simulation output. The higher the number, the greater the detail. The output level has the following values:

1. 10 = summary information
2. 20 = order information
3. 30 = job information
4. 40 = activity information
5. 50 = unit information

The final input to PROCFIL is the color (BLUE or RED) and X and Y coordinates of each ammunition supply point. Ammunition supply points are determined by the user from the scenario to be modeled.

**IMPORTANT:** Changes in the data base (i.e., number of situations, techniques, etc.) require the user to update PROCFIL before running a simulation program.

#### *PROCFIL: Input Instructions*

1. Number of Situations    Number of Ammunition Supply Points
2. Number of ESY    Number of TEC    Number of TSK    Number of SJO  
    Number of MJO    Number of SRC    Number of EUT    Number of TUT
3. File Numbers for (ESY TEC TSK SJO MJO SRC EUT TUT)
4. Report Flags for (ESY TEC TSK SJO MJO SRC EUT TUT)
5. Output Level (10, 20, 30, 40, or 50)
6. Color of Ammunition Supply Point (BLUE or RED)
7. X Location    Y Location

NOTE: REPEAT 6 AND 7 FOR EACH AMMUNITION SUPPLY POINT.

#### *PROCFIL: Sample Input Data*

```

1 2                (number of situations, number of ammunition supply points)
13 56 17 1 19 3 4 2 (number of ESY, TEC, TSK, SJO, MJO, SRC, EUT, and TUT)
9 11 13 15 17 19 21 23 25 (file numbers for ESY, TEC, TSK, SJO, MJO, SRC, EUT, and TUT)
0 0 0 0 0 1 1 1 0 (report flags for ESY, TEC, TSK, SJO, MJO, SRC, EUT, and TUT)*
50                (output level)
BLUE              (color of ammunition supply point)
85 180            (X location, Y location)
BLUE              (color of ammunition supply point)
136 103           (X location, Y location)

```

\*The ninth report flag, interface, must be set at 0.

#### **Assignment File (DECVAX 11/780 Only)**

A data file named ASSGN.OLD must be created for model operation on the VAX/VMS operating system. This file frees the user from having to input each file name before each run of the model. The user may give the first nine data files any desired name within the previously defined convention ((xxx) ESY, (xxx) EUT, (xxx) TSK, etc.). Each of these file names, however, must be translated into names that the Engineer Module's internal operating system will recognize. The ASSGN.OLD file accomplishes this task.

In this example, CORDIV.PROCESS.ENGR is the name of the account where the data files reside and D86 is the three-character prefix ((xxx)) to the file names:

#### *ASSGN.OLD: Sample Input Data*

```
ASSIGN [CORDIV.PROCESS.ENGR] D86ESY.DAT SIMU09
ASSIGN [CORDIV.PROCESS.ENGR] D86TEC.DAT SIMU11
ASSIGN [CORDIV.PROCESS.ENGR] D86TSK.DAT SIMU13
ASSIGN [CORDIV.PROCESS.ENGR] D86SJO.DAT SIMU15
ASSIGN [CORDIV.PROCESS.ENGR] D86MJO.DAT SIMU17
ASSIGN [CORDIV.PROCESS.ENGR] D86SRC.DAT SIMU19
ASSIGN [CORDIV.PROCESS.ENGR] D86EUT.DAT SIMU21
ASSIGN [CORDIV.PROCESS.ENGR] D86TUT.DAT SIMU23
ASSIGN [CORDIV.PROCESS.ENGR] D86JOBS.DAT SIMU47
ASSIGN [CORDIV.PROCESS.ENGR] PSEUPROC.OLD SIMU31
ASSIGN OUT.USE                               SIMU33
ASSIGN OUT.HIS                               SIMU35
```

#### **Operating Procedures (Boeing Cyber Computer Only)**

After the user has created the eight basic data files, an order stream file, and *updated the procedure file*, a simulation program may be run. The eight major data files are considered as two types of data: standard operating procedures (SOP) and force structure (STRUCT). The SOP consists of the engineer system's techniques, tasks, single job orders, and multiple job orders. The STRUCT consists of the standard requirements codes, engineer units, and tactical units. This division was made since it was thought the SOP would not change very often, but the user might wish to change the force structure and make separate runs using the same order stream.

The engineer systems data file ((xxx) ESY) *must* be assigned to SIMU09, the techniques data file ((xxx) TEC) to SIMU11, and so on.

The assignment file also assigns the Engineer Module output which is created during each simulation run. Outputs are described in Chapter 3.

All files in the SOP group must have identical three-character prefixes ((xxx)). The three files in the STRUCT group must have identical prefixes. (See Table 3.)

The user is assumed to have some experience with automated data processing (ADP) systems. Instructions are given for model operation on the Boeing Computer system. To create and update the data base, see the *MAINSTREAM-EKS Interactive Timesharing (KIT) Users Manual*.

To log onto the Boeing system, the user must dial the local Boeing telephone number to activate a terminal session. The user must press the return key to (1) start a session,



**Table 3  
File Prefixes**

SOP Group	STRUCT Group	Order Stream
1. CD1ESY	6. D86SRC	9. TSTJOBS
2. CD1TEC	7. D86EUT	
3. CD1TSK	8. D86TUT	
4. CD1SJO		
5. CD1MJO		

and (2) after each input line is typed. The Boeing system will return with system messages and the following prompts:

<i>System Prompt</i>	<i>User Response</i>
1. SELECT DESIRED SERVICE:	EKS1
2. USERNUMBER:	XXX
3. PASSWORD:	YYY
4. RECOVER/USER ID:	ZZZ

The user's response will depend on the local ADP assignment of a user number and password. The RECOVER/USER ID is an alphanumeric response by the user, such as his or her name.

The following paragraphs give examples of the five types of output commands.

1. How to submit a simulation program.
2. How to check on the progress of a simulation run if response time is slow.
3. How to get a computer listing of simulation output.
4. How to get an alphabetical listing of all data base input.
5. How to get an abbreviated listing of the data base input files.

#### *To Submit a Job*

BEGIN, SEND,, PRE = <xxx>, STRUCT = <xyz>,  
WAIT = YES/NO, EDIT = YES/NO, REMOTE = YES/NO, SOP = <zzz>

PRE = <xxx> is the prefix for the job stream and output (one to three characters).  
Order stream file must be called <xxx> JOBS.

If PRE = TST, order stream = TSTJOBS.

STRUCT = <xyz> is the prefix for command structure files.

WAIT = YES, if user wants interactive output (default).

WAIT = NO, if user does not want interactive output.

EDIT = YES, if user wants to edit output when the job is done (default).

EDIT = NO, if user does not want to edit output.

REMOTE = NO. Output becomes edit file (default).

REMOTE = YES. Output goes to remote job terminal.

SOP = (zzz) is the prefix for standard operating procedure. Files: ZZZESY, ZZZTEC, ZZZTSK, ZZZSJO, ZZZMJO.

*To Check on a Job*

BEGIN, CKJOB, PRE = (xxx), EDIT = YES/NO

PRE and EDIT are defined as explained above.

*To Print Files*

BEGIN, PRINT, (filename), PS = SHFT, NUM = (n)

If PRE = TST, output (filenames) are TSTOUT and TSTHOUT.

PS = Print Shift

NUM = Number of copies (1 is default)

*To Obtain an Alphabetized Data Base List of Input*

PURGE, JEROUT

BEGIN, REPORT,, (xxx) ESY, (xxx) TEC, (xxx) TSK, (xxx) SJO,  
(xxx) MJO, (xxx) SRC, (xxx) EUT, (xxx) TUT

*To Obtain an Alphabetical List of Techniques, Tasks, or Single Job Orders*

GET, JEROUT

BEGIN, EXTRACT,, JEROUT

BEGIN, SORTLST,, NUM = n

(filename)

n = number of copies

**Operating Procedures (DEC VAX 11/780 Only)**

After the user has created the eight basic data files, an order stream file, an assignment file, and updated the procedure file, a simulation program may be run.

To log onto the VAX/VMS system, the user must press the return key to (1) start the session, and (2) after each input line is typed. The system will respond with the following prompts and system messages:

<i>System Prompt</i>	<i>User Response</i>
Username:	ABCDEF
Password:	LMNOPQ

The user response will depend on the local ADP assignment of a user name and password. To create or change the data base files, the user should consult the "VAX-11 EDT Editor Reference Manual," in the *VAX/VMS Users Manual, Volume 3A*.

When the user has correctly logged in, the system will respond with an \$ prompt. To run the model, the user must give the following inputs in response to the prompts:

<i>System Prompt</i>	<i>User Response</i>
\$	@[xxx.xxxx] assgn.old
\$	simrun [zzz] salone2

Square brackets enclose the names of the accounts where the named files reside. In this example, the ASSIGN.OLD file resides in account xxx.xxxx and the executable Engineer Module (SALONE2.EXE) resides in account zzz.

### 3 OUTPUT

The Engineer Module program output has two parts: a file named (xxx) OUT on the Boeing Cyber or OUT.USE on the VAX 11/780, and a file named (xxx) HOUT on the Cyber or OUT.HIS on the VAX. The (xxx) is the same prefix as the (xxx) JOBS file prefix that contained the order stream (see **Operating Procedures**, Chapter 2).

The (xxx) OUT file contains:

1. Ammunition supply points (their location)
2. Standard requirements code
3. Engineer units (their location and support relationships)
4. Tactical units (their support relationships)
5. Simulation run time (hours)
6. Total jobs generated, number completed, number infeasible
7. Total orders generated, number completed, number infeasible
8. Statistics for engineering units (hours)
  - a. Not assigned
  - b. Queued

- c. Assigned
- d. Wait at work site
- e. Wait halted
- f. Site work
- g. Ammunition supply point upload
- h. Move to work site
- i. Model move from work site back to parent location.

An example of <xxx> OUT file is shown in Figure 4.

The <xxx> HOUT file is a timeline trace which starts at time 0 and ends with the end of the simulation run. The output level is set as noted in PROCFIL and has the following values:

- 1. 10 = summary information
- 2. 20 = order information
- 3. 30 = job information
- 4. 40 = activity information
- 5. 50 = unit information.

Output level 50 gives a detailed trace of each unit (Figure 5). The fields have the following values:

- 1. Five-character order abbreviation
- 2. The order number and a two-character order abbreviation
- 3. A sequence number for post-processing
- 4. Clock time
- 5. Order number pointer (six digits)
- 6. Job number pointer (six digits)
- 7. Unit number
- 8. Activity description.

```

1      1      AMMUNITION SUPPLY POINTS (ASPS)
      COLOR      X.LOCATION      Y.LOCATION
      BLUE      31.00      31.00
1      3 SRC TABLES

FOR BLUE SRC      1      WITH TITLE ENG.PLT.DIV
ENGR SYSTEM QUANTITY      TITLE
      3.0      SQUAD
      1.0      CEV
      2.0      ACE

FOR BLUE SRC      2      WITH TITLE ENG.CO.DIV.POOL
ENGR SYSTEM QUANTITY      TITLE
      1.0      GEMSS
      1.0      2.5 LOADER
      6.0      AVL8
      2.0      SLUFAE

FOR BLUE SRC      3      WITH TITLE NONE
ENGR SYSTEM QUANTITY      TITLE
      0.0
1      5      ENGR UNIT TABLES

FOR BLUE ENGR UNIT      1      WITH TITLE 1ST.PLT.A.CO
USING SRC NUMBER      1 WITH TITLE ENG.PLT.DIV
ENGR UNIT --- PARENT SUPPORTED TAC UNIT      X.LOC      Y.LOC
      5      1      32.0      33.0

FOR BLUE ENGR UNIT      2      WITH TITLE 2ND.PLT.A.CO
USING SRC NUMBER      1 WITH TITLE ENG.PLT.DIV
ENGR UNIT --- PARENT SUPPORTED TAC UNIT      X.LOC      Y.LOC
      5      2      33.0      34.0

FOR BLUE ENGR UNIT      3      WITH TITLE 3RD.PLT.A.CO
USING SRC NUMBER      1 WITH TITLE ENG.PLT.DIV
ENGR UNIT --- PARENT SUPPORTED TAC UNIT      X.LOC      Y.LOC
      5      3      33.0      31.0

FOR BLUE ENGR UNIT      4      WITH TITLE A.CO.POOL
USING SRC NUMBER      2 WITH TITLE ENG.CO.DIV.POOL
ENGR UNIT --- PARENT SUPPORTED TAC UNIT      X.LOC      Y.LOC
      5      0      33.0      31.0

FOR BLUE ENGR UNIT      5      WITH TITLE A.CO.HQ
USING SRC NUMBER      3 WITH TITLE NONE

```

Figure 4. Example (xxx) OUT file.

ENGR UNIT --- PARENT SUPPORTED TAC UNIT X.LOC Y.LOC  
 NONE 0 26.0 31.0

NUMBER OF UNITS TO BE CREATED 28  
 TACTICAL UNIT TABLES

FOR BLUE TACTICAL UNIT 1 WITH TITLE 5TH.BN.1ST.BDE

PARENT SUPPORT ENGR UNIT  
 NONE 1

FOR BLUE TACTICAL UNIT 2 WITH TITLE 6TH.BN.1ST.BDE

PARENT SUPPORT ENGR UNIT  
 NONE 2

FOR BLUE TACTICAL UNIT 3 WITH TITLE 7TH.BN.1ST.BDE

PARENT SUPPORT ENGR UNIT  
 NONE 3

FOR BLUE TACTICAL UNIT 4 WITH TITLE 8TH.BN.1ST.BDE

PARENT SUPPORT ENGR UNIT  
 NONE 4

SIMULATION STOPPED AT 20.34 HOURS

TOTAL NUMBER OF JOBS 9 NUMBER COMPLETED 9 NUMBER INFEASIBLE 0  
 TOTAL NUMBER OF JOBS 1 NUMBER COMPLETED 1 NUMBER INFEASIBLE 0

STATISTICS FOR ENGINEERING UNITS IN HOURS										
UNIT	SYSTEM	ENGR	NOT	ASSIGNED	WAIT	WAIT	SITE	ASP	MOVE	MODEL
					AT A.S.	HALTED	WORK	UPLOAD		MOVE
1	SQUAD	7.51	0.	0.	.05	0.	12.70	0.	.04	.04
2	SQUAD	7.51	0.	0.	.05	0.	12.70	0.	.04	.04
3	SQUAD	7.51	0.	0.	.05	0.	12.70	0.	.04	.04
4	CEV	4.00	0.	0.	10.03	0.	5.00	0.	.13	.13
5	ACE	0.	0.	0.	5.17	0.	15.00	0.	.09	.09
6	ACE	0.	0.	0.	5.17	0.	15.00	0.	.09	.09
7	SQUAD	20.34	0.	0.	0.	0.	0.	0.	0.	0.
8	SQUAD	20.34	0.	0.	0.	0.	0.	0.	0.	0.
9	SQUAD	20.34	0.	0.	0.	0.	0.	0.	0.	0.
10	CEV	20.34	0.	0.	0.	0.	0.	0.	0.	0.
11	ACE	20.34	0.	0.	0.	0.	0.	0.	0.	0.
12	ACE	20.34	0.	0.	0.	0.	0.	0.	0.	0.
13	SQUAD	20.34	0.	0.	0.	0.	0.	0.	0.	0.
14	SQUAD	20.34	0.	0.	0.	0.	0.	0.	0.	0.
15	SQUAD	20.34	0.	0.	0.	0.	0.	0.	0.	0.
16	CEV	20.34	0.	0.	0.	0.	0.	0.	0.	0.
17	ACE	20.34	0.	0.	0.	0.	0.	0.	0.	0.
18	ACE	20.34	0.	0.	0.	0.	0.	0.	0.	0.
19	GEMAS	19.48	0.	0.	0.	0.	.77	0.	.05	.05
20	2.5 LOA	8.45	0.	0.	1.65	0.	10.00	0.	.12	.12
21	AVLB	20.34	0.	0.	0.	0.	0.	0.	0.	0.
22	AVLB	20.34	0.	0.	0.	0.	0.	0.	0.	0.
23	AVLB	20.34	0.	0.	0.	0.	0.	0.	0.	0.
24	AVLB	20.34	0.	0.	0.	0.	0.	0.	0.	0.
25	AVLB	20.34	0.	0.	0.	0.	0.	0.	0.	0.
26	AVLB	20.34	0.	0.	0.	0.	0.	0.	0.	0.
27	SLUFAR	20.34	0.	0.	0.	0.	0.	0.	0.	0.
28	SLUFAR	20.34	0.	0.	0.	0.	0.	0.	0.	0.

EXIT 0

Figure 4. (Cont'd).

**Figure 5. Example  $\langle xxx \rangle$  HOUT file.**

## APPENDIX A: BIBLIOGRAPHY

### General

- Kiviat, P. J., et al., *SIMSCRIPT II.5*, ed. E. C. Russell (C.A.C.I. Inc., 1975).  
*MAINSTREAM-EKS Interactive Timesharing (KIT) Users Manual* (Boeing Computer Services, Inc., 1977).  
*VAX/VMS Users Manual, Volume 3A* (Software Distribution Center, Digital Equipment Corporation, 1980).  
*Historical Evaluation of Barrier Effectiveness* (Historical Evaluation and Research Organization, 1974).  
*The Value of Field Fortification in Modern Warfare* (Historical Evaluation and Research Organization, 1979).  
*Engineer Family of Systems Study (E-FOSS)* (U.S. Army Engineer School, 1979).  
*Army Modeling Improvement Program Master Plan* (U.S. Army Combined Arms Center, 12 June 1981).  
*Planning Guide for the Use of U.S. Army Floating Equipment* (U.S. Army Engineer School, 1980).

### Field Manuals

- FM 5-1, *Engineer Troop Organizations and Operations*.  
FM 5-15, *Field Fortifications*.  
FM 5-25, *Explosives and Demolitions*.  
FM 5-34, *Engineer Field Data*.  
FM 5-35, *Engineer Reference and Logistical Data*.  
FM 5-100, *Engineer Combat Operations*.  
FM 90-7, *Obstacles*.  
FM 90-13, *River Crossing Operations*.

### Army Training Evaluation Program

- ARTEP 5-25, *Engineer Units in Airborne, Air Assault, Infantry Divisions, and Separate Brigades*.  
ARTEP 5-35, *Engineer Combat Battalion (Corps)*.  
ARTEP 5-64, *Engineer Bridge Company*.  
ARTEP 5-115, *Engineer Combat Battalion (Heavy)*.  
ARTEP 5-145, *Engineer Battalion, Mechanized and Armored Division*.

### Threat Data

- FM 30-102, *Opposing Forces, Europe*.  
*Soviet Army Operations*, IAG-13-U-78 (Department of the Army, April 1978).  
*Soviet and Warsaw Pact River Crossing: Doctrine and Capabilities*, DDI-1150-13-77 (Defense Intelligence Agency [DIA], May 1977).  
*Soviet/Warsaw Pact Ground Force Camouflage and Concealment Techniques*, DDI-1100-161-78 (DIA, January 1978).  
*Soviet Tank Company Tactics*, DDI-1120-129-76 (DIA, May 1976).  
*The Soviet Motorized Rifle Company*, DDI-1100-77-76 (DIA, October 1976).  
*The Soviet Motorized Rifle Battalion*, DDB-1100-197-78 (DIA, September 1978).  
*Organization and Equipment of the Soviet Army*, Handbook 550-2 (Combined Arms Combat Development Activity, July 1980).



## APPENDIX B: SIMULATION CONTROL ERRORS

The following errors are caused by user error and are ultimately fatal.

1. \*\*\*\*\*WARNING\*\*\*\*\* NUMBER OF ENGR SYSTEMS READ = \_\_\_\_\_ ,  
NUMBER EXPECTED WAS \_\_\_\_\_ .
2. \*\*\*\*\*WARNING\*\*\*\*\* NUMBER OF TECH READ = \_\_\_\_\_ ,  
NUMBER EXPECTED WAS \_\_\_\_\_ .
3. \*\*\*\*\*WARNING\*\*\*\*\* NUMBER OF TASKS READ = \_\_\_\_\_ ,  
NUMBER EXPECTED WAS \_\_\_\_\_ .
4. \*\*\*\*\*WARNING\*\*\*\*\* NUMBER OF SJOS READ = \_\_\_\_\_ ,  
NUMBER EXPECTED WAS \_\_\_\_\_ .
5. \*\*\*\*\*WARNING\*\*\*\*\* NUMBER OF MJOS READ = \_\_\_\_\_ ,  
NUMBER EXPECTED WAS \_\_\_\_\_ .
6. \*\*\*\*\*WARNING\*\*\*\*\* NUMBER OF SRCS READ = \_\_\_\_\_ ,  
NUMBER EXPECTED WAS \_\_\_\_\_ .
7. \*\*\*\*\*WARNING\*\*\*\*\* NUMBER OF ENGR UNITS READ = \_\_\_\_\_ ,  
NUMBER EXPECTED WAS \_\_\_\_\_ .
8. \*\*\*\*\*WARNING\*\*\*\*\* NUMBER OF TACTICAL UNITS READ = \_\_\_\_\_ ,  
NUMBER EXPECTED WAS \_\_\_\_\_ .

These errors indicate the user has fewer or more systems (techniques, tasks, single job orders, multiple job orders, standard requirements codes, engineer units, or tactical units) than those specified in PROCFIL. The user should edit PROCFIL to correct the number of engineer systems, techniques, tasks, single job orders, multiple job orders, standard requirements codes, engineer units, and/or tactical units (#TEC, #TSK, #SJO, #MJO, #SRC, #EUT, #TUT) and rerun.

CERL DISTRIBUTION

Chief of Engineers  
ATTN: Tech Monitor  
ATTN: DAEM-ASI-L (2)  
ATTN: DAEM-CCP  
ATTN: DAEM-CV  
ATTN: DAEM-CWE  
ATTN: DAEM-CWM-B  
ATTN: DAEM-CWO  
ATTN: DAEM-CWP  
ATTN: DAEM-MPC  
ATTN: DAEM-MPE  
ATTN: DAEM-MPO  
ATTN: DAEM-MPB-A  
ATTN: DAEM-ED  
ATTN: DAEM-RDC  
ATTN: DAEM-RDM  
ATTN: DAEM-RM  
ATTN: DAEM-ZC  
ATTN: DAEM-ZCE  
ATTN: DAEM-ZCI  
ATTN: DAEM-ZCM

FESA, ATTN: Library 22060

FESA, ATTN: DET III 79906

US Army Engineer Districts

ATTN: Library  
Alaska 99501  
Al Bacin 09616  
Albuquerque 87103  
Baltimore 21203  
Buffalo 14207  
Charleston 29402  
Chicago 60604  
Detroit 48231  
Far East 96301  
Fort Worth 76102  
Galveston 77550  
Huntington 25721  
Jacksonville 32232  
Japan 96343  
Kansas City 64106  
Little Rock 72203  
Los Angeles 90053  
Louisville 40201  
Memphis 38103  
Mobile 36628  
Nashville 37202  
New Orleans 70160  
New York 10007  
Norfolk 23510  
Omaha 68102  
Philadelphia 19106  
Pittsburgh 15222  
Portland 97208  
Riyadh 09038  
Rock Island 61201  
Sacramento 95814  
San Francisco 94105  
Savannah 31402  
Seattle 98126  
St. Louis 63101  
St. Paul 55101  
Tulsa 74102  
Vicksburg 39180  
Wallis Wallis 99362  
Wilmington 28401

US Army Engineer Divisions

ATTN: Library  
Europe 09757  
Huntsville 35807  
Lower Mississippi Valley 39180  
Middle East 09038  
Middle East (Rear) 22601  
Missouri River 68101  
New England 02154  
North Atlantic 10007  
North Central 60605  
North Pacific 97208  
Ohio River 45201  
Pacific Ocean 96858  
South Atlantic 30303  
South Pacific 94111  
Southwestern 75202

US Army Europe

HQ, 7th Army Training Command 09114  
ATTN: AETTG-DEM (5)  
Hq, 7th Army ODCS/Engr. 09403  
ATTN: AEAEN-EN (4)  
V. Corps 09079  
ATTN: AETVDEN (5)  
VII. Corps 09154  
ATTN: AETSDEM (5)  
21st Support Command 09325  
ATTN: AEREN (5)  
Berlin 09742  
ATTN: AERBA-EN (2)  
Southern European Task Force 09168  
ATTN: AERSE-ENG (3)  
Installation Support Activity 09403  
ATTN: ARUES-EP

8th USA, Korea  
ATTN: EAPF-B 96271  
ATTN: EAPF-P 96259  
ATTN: EAPF-T 96212

8th USA, Korea

ATTN: EAPF-B 96271  
ATTN: EAPF-P 96259  
ATTN: EAPF-T 96212

ROK/US Combined Forces Command 96301  
ATTN: EUSA-ENG-CFC/Engr

USA Japan (USARJ)

Ch. PE Div. AJEM-PE 96343  
Fac Engr (Monabu) 96343  
Fac Engr (Okinawa) 96331

Rocky Mt. Area 80903

Area Engineer, AEDC-Area Office  
Arnold Air Force Station, TN 37389

Western Area Office, CE  
Vandenberg AFB, CA 93437

416th Engineer Command 60623  
ATTN: Facilities Engineer

US Military Academy 10996

ATTN: Facilities Engineer  
ATTN: Dept of Geography &  
Computer Science  
ATTN: DSCPER/NAEN-A

Engr. Studies Center 20315

ATTN: Library

AMNRC, ATTN: DRXNR-WB 02172

USA ARRCOM 61299

ATTN: DRGIS-RF-I  
ATTN: DMSAR-IS

DARCOM - Dir., Inst., & Svcs.

ATTN: Facilities Engineer  
ARRADCOM 07401  
Aberdeen Proving Ground 21005  
Army Mater. and Mechanics Res. Ctr.  
Corpus Christi Army Depot 78419  
Harry Diamond Laboratories 20783  
Dugway Proving Ground 84022  
Jefferson Proving Ground 47250  
Fort Monmouth 07703  
Letterkenny Army Depot 17201  
Natick R&D Ctr. 01760  
New Cumberland Army Depot 17070  
Pueblo Army Depot 81001  
Red River Army Depot 75501  
Redstone Arsenal 35809  
Rock Island Arsenal 61299  
Savanna Army Depot 81074  
Sharpe Army Depot 14541  
Tobyhanna Army Depot 18466  
Tooele Army Depot 84074  
Watervliet Arsenal 12189  
Yuma Proving Ground 85364  
White Sands Missile Range 88002

DLA ATTN: DLA-WI 22314

FORSCOM

FORSCOM Engineer, ATTN: APEN-PE  
ATTN: Facilities Engineer  
Fort Buchanan 00934  
Fort Bragg 28307  
Fort Campbell 42223  
Fort Carson 80913  
Fort Devens 01433  
Fort Drum 13601  
Fort Hood 76544  
Fort Indianapolis (Cap 17003  
Fort Irwin 92311  
Fort Sam Houston 78234  
Fort Lewis 98433  
Fort McCoy 54656  
Fort McPherson 30330  
Fort George G. Meade 20755  
Fort Ord 93941  
Fort Polk 71459  
Fort Richardson 99505  
Fort Riley 66442  
Presidio of San Francisco 94129  
Fort Sheridan 60037  
Fort Stewart 31333  
Fort Walworth 99703  
Vancouver Bks. 96660

NSC

ATTN: NSLO-P 78234  
ATTN: Facilities Engineer  
Pittsboro AMC 80240  
Walter Reed AMC 20012

INSCOM - Ch. Instl. Div.

ATTN: Facilities Engineer  
Arlington Hall Station (2) 22212  
Vint Hill Farms Station 22186

NDW

ATTN: Facilities Engineer  
Cameron Station 22314  
Fort Lesley J. McNair 20319  
Fort Myer 22211

NTMC

ATTN: NTMC-SA 20315  
ATTN: Facilities Engineer  
Oakland Army Base 94626  
Rayome MOT 07002  
Sunny Point MOT 28461

WARADCOM, ATTN: DRDMA-F 071160

TARCOM, Fac. Div. 48090

TRADOC

HQ, TRADOC, ATTN: ATEN-PE  
ATTN: Facilities Engineer  
Fort Belvoir 22060  
Fort Benning 31905  
Fort Bliss 79916  
Carlisle Barracks 17013  
Fort Chaffee 72902  
Fort Dix 08640  
Fort Eustis 23604  
Fort Gordon 30905  
Fort Hamilton 11252  
Fort Benjamin Harrison 46216  
Fort Jackson 29207  
Fort Knox 40121  
Fort Leavenworth 66027  
Fort Lee 23801  
Fort McClellan 36205  
Fort Monroe 23651  
Fort Rucker 36362  
Fort Sill 73503  
Fort Leonard Wood 65473

TSARCOM, ATTN: STSAS-P 63120

USACC

ATTN: Facilities Engineer  
Fort Huachuca 85613  
Fort Ritchie 21719

WESTCOM

ATTN: Facilities Engineer  
Fort Shafter 96858

SHAPE 09055

ATTN: Survivability Section, OCB-OPS  
Infrastructure Branch, LANDA

HQ USKUCOM 09128

ATTN: ECI 4/7-LOE

Fort Belvoir, VA 22060

ATTN: ATZA-DTE-EM

ATTN: ATZA-DTE-SM

ATTN: ATZA-PE

ATTN: Engr. Library

ATTN: Canadian Liaison Office (2)

ATTN: LWR Library

Cold Regions Research Engineering Lab 09755

ATTN: Library

ETL, ATTN: Library 22060

Waterways Experiment Station 39180

ATTN: Library

HQ, XVIII Airborne Corps and 28307

Fort Bragg

ATTN: AFZA-PE-EE

Chanute AFB, IL 61868

1345 CES/DK, Stop 27

Norton AFB 92409

ATTN: AFNCK-MK/WEK

Tyndall AFB, FL 32403

AFESC/Engineering & Service Lab

NAFEC

ATTN: ROT&E Liaison Office  
Atlantic Division 23511  
Chesapeake Division 20374  
Southern Division 29411  
Pacific Division 96860  
Northern Division 19112  
Western Division 64066  
ATTN: Sr. Tech. FAC-OST 22332  
ATTN: Asst. CDR RAD, PAC-03 22332

NCRL 93041

ATTN: Library (Code LOBA)

Defense Technical Info. Center 22314

ATTN: DDA (12)

Engineering Societies Library 10017

New York, NY

National Guard Bureau 20310

Installation Division

US Government Printing Office 22304

Receiving Section/Repository Copies (7)

# Resource Allocation Team Distribution

Chief of Engineers  
ATTN: DAEN-MPO-B  
ATTN: DAEN-MPR  
ATTN: DAEN-MP2-A  
ATTN: DAEN-ZCI  
ATTN: DAEN-ZCP

US Army Engineer District  
New York 10007  
ATTN: Chief, Design Br  
Pittsburgh 15222  
ATTN: Chief, Engr Div  
Philadelphia 19106  
ATTN: Chief, NAFEN-D  
Baltimore 21203  
ATTN: Chief, Engr Div  
Norfolk 23510  
ATTN: Chief, NAOEN-D  
Wilmington 28401  
ATTN: Chief, SAWEN-PP  
ATTN: Chief, SAWEN-PM  
Charleston 29402  
ATTN: Chief, Engr Div  
Savannah 31402  
ATTN: Chief, SASAS-L  
Jacksonville 32232  
ATTN: Env Res Br  
Mobile 36128  
ATTN: Chief, SAMEN-D  
Nashville 37202  
ATTN: Chief, ORNED-P  
Memphis 38103  
ATTN: Chief, LMED-P  
Vicksburg 39180  
ATTN: Chief, Engr Div  
Louisville 40201  
ATTN: Chief, Engr Div  
St Paul 55101  
ATTN: Chief, ED-D  
Chicago 60604  
ATTN: Chief, NCCPD-ER  
St Louis 63101  
ATTN: Chief, ED-B  
ATTN: Chief, ED-D  
Kansas City 64106  
ATTN: Chief, Engr Div  
Omaha 68102  
ATTN: Chief, Engr Div  
Toledo 44102  
ATTN: Chief, Engr Div  
Albuquerque 87103  
ATTN: Chief, Engr Div  
San Francisco 94105  
ATTN: Chief, Engr Div  
New Orleans 70160  
ATTN: Chief, LMED-DG  
Sacramento 95814  
ATTN: Chief, SPKED-D  
Far East 96301  
ATTN: Chief, Engr Div  
Seattle 98124  
ATTN: Chief, NPSEN-PL-ER  
Santa Maria 99362  
ATTN: Chief, Engr Div  
Alaska 99501  
ATTN: Chief, NPASA-R

US Army Engineer Division  
New England 02154  
ATTN: Chief, MEDED-T  
North Atlantic 10007  
ATTN: Chief, NADEN-T  
Middle East (Rear) 22601  
ATTN: Chief, MEDED-T  
South Atlantic 30303  
ATTN: Chief, SADEN-TS  
Huntsville 35807  
ATTN: Chief, HNOED-CS  
Lower Mississippi Valley 39180  
ATTN: Chief, PD-R  
Ohio River 45201  
ATTN: Chief, Engr Div  
North Central 60605  
ATTN: Chief, Engr Div

US Army Engineer Division  
Southwestern 75202  
ATTN: Chief, SMDED-TA  
South Pacific 94111  
ATTN: Chief, SPDED-TG  
Pacific Ocean 96858  
ATTN: Chief, Engr Div  
ATTN: Chief, PODED-M  
North Pacific 97208  
ATTN: Chief, Engr Div

6th US Army 94129  
ATTN: AFKC-EN

7th US Army 09407  
ATTN: AETTM-HRD-END

West Point, NY 10996  
ATTN: Dept of Mechanics  
ATTN: Library

Ft. Belvoir, VA 22060  
ATTN: Learning Resources Center  
ATTN: ATSE-TD-TL (2)  
ATTN: British Liaison Officer (5)

Ft. Clayton Canal Zone 34004  
ATTN: OFAE

Ft. Leavenworth, KS 66027  
ATTN: ATZLCA-SA

Ft. Lee, VA 23801  
ATTN: DRXMC-D (2)

Ft. McPherson, GA 30330  
ATTN: AFEN-CD

Ft. Monroe, VA 23651  
ATTN: ATEN-AD (3)  
ATTN: ATEN-C

Ft. Richardson, AK 99505  
ATTN: AFZT-FE-E

Naval Facilities Engineer Command  
ATTN: Code 04  
Alexandria, VA 22332

NCEL 93043  
ATTN: Morell Library

Patrick AFB, FL 32925  
ATTN: XRO

Tinker AFB, OK 73145  
2854 ABG/DEEE

Tyndall AFB, FL 32403  
AFESC/PRT

Building Research Advisory Board 20418

Transportation Research Board 20418

Airports and Construction Services Dir  
Ottawa, Ontario, Canada K1A 0N8

Division of Building Research  
Ottawa, Ontario, Canada K1A 0R6

National Defense Headquarters  
Ottawa, Ontario, Canada K1A 0K2

Ms. Dee Scholes  
Computer Science Corporation  
Defense Systems Division  
304 W. Route 38  
Morristown, NJ 08057

Engineer Study Center  
ATTN: Doug Lehman  
6500 Brooke Lane  
WASH DC 20315

Commander, TRADOC  
ATTN: ATCD-A/Mark Murray  
Fort Monroe, VA 23651

Director, AMSAA  
ATTN: DRXSX-GB/Lee Meredith  
Aberdeen Proving Grounds, MD 21005

CDR USACE (DAEN-DRD/John Henry)  
WASH DC 20314

USA TRASANA  
ATTN: ATAA-TGM/Keith Thorpe  
White Sands Missile Range, NM 88002

Commander, U.S. Army Engineer School  
ATTN: ATEA-CDE/CPT Cliff Clausen  
Fort Belvoir, VA 22060

CAC & Fort Leavenworth  
ATTN: ATZL-CAC-A  
Fort Leavenworth, KS 66027

Director, U.S. Army Concepts Analysis Agency  
CSCA-FAS (Major Alvord)  
8120 Woodmont  
Bethesda, MD 20014

Pentagon  
SAUS-OR/Herb Fallin  
Room 2E 621  
WASH DC 20310

Gerald W. Tunage  
Mobility Systems Division  
Geotechnical Laboratory  
USA Waterways Experiment Station  
P.O. Box 631  
Vicksburg, MS 39180

U.S. Army Engineer District, Memphis  
ATTN: CPT Van Horn  
608 Clifford Davis Federal Building  
Memphis, TN 38103

CPT Edward Wright  
Executive Officer  
HQ 2nd BN, 2nd Brigade  
Fort Leonard Wood, MO 63475

Department of the Army  
HQ, USA, Europe, and 7th Army  
Office of the Deputy Chief of Staff  
ATTN: Mr. A. Fleming  
APO New York 09403

Engineer modeling study. -- Champaign, Ill : Construction Engineering  
Research Laboratory ; available from NTIS.  
3v. (Technical report / Construction Engineering Research Laboratory ;  
p-131)

Contents: v.1. Executive summary / by John Evans. -- v.2. Users  
manual / by Gerald Brown, Hugh Henry. -- v.3. CORDIVEM/Engineer Module  
Interface manual / by Carlton Mills.

1. War games. 2. Military engineering -- models. I. Evans, John.  
II. Brown, Gerald J. III. Henry, Hugh IV. Mills, Carlton. V. Series:  
Technical report (Construction Engineering Research Laboratory (U.S.));  
P-131.

END  
FILMED

4-86

DTIC